

LED ZX LITE Fixture 720W



Spectrum 500 600 700 400 800

- **☑** Superior light output
- **☑** Full spectrum LED
- **☑** Suitable for both vegetative and flowering stages of plant growth
- **☑** Rope ratchets included for easy hanging

Features

- Lightweight and easy to install
- Foldable for easy storage
- The new 720W Driver-Boosted Six Bar Fixture is designed to deliver high performance and efficiency. It is powered and controlled by the 720W LED Driver, which can be directly attached to the fixture. The fixture itself is lightweight and easy to install, and the included rope ratchets enable convenient height adjustments as plants grow.
- This fixture provides a full spectrum of light, making it well-suited for both the vegetative and flowering stages of plant growth. With the included dimmable driver, the light intensity can be adjusted from 280W to the full boosted power of 720W.















Specifications

Product Model		LEDzx F720B	LEDzx F720B			
Product code		80.01.0707	80.01.0707			
Input power		720W	720W			
Dimming		150W, 230W, 320V	150W, 230W, 320W, 420W, 520W, 630W, 720W, EXT/0-10V			
Input voltage		AC 120V-277V	AC 120V-277V			
Light output PPF		1950 μmol/s	1950 μmol/s			
Efficiency		2.70 μmol/J	2.70 μmol/J			
Input frequency		50/60Hz	50/60Hz			
Light distribution		120°	120°			
Mounting height		8"- 24" (20-60cm) a	8"- 24" (20-60cm) above canopy			
Operating temperature		-20°C~35°C	-20°C~35°C			
Operating humidity		0~95%	0~95%			
Thermal management		Passive	Passive			
Power factor		≥ 0.97	≥ 0.97			
Total harmonic distortion		≤ 10%	≤ 10%			
Requirement of installment		Comply with ETL/CE	Comply with ETL/CE/EAC certificate			
Lifetime L90		≥ 50,000hrs	≥ 50,000hrs			
IP rating		IP65	IP65			
Product dimensions		1080x1100x83mm	1080x1100x83mm			
Product weight		6.4 KG	6.4 KG			
Packaging method		1PC/Carton (LED fixt	1PC/Carton (LED fixture with Driver)			
Packing dimensions		1140x110x585mm	1140x110x585mm			
Gross weight		8.5 KG	8.5 KG			
Loading Quantity		20GP: 380 Cartons	20GP: 380 Cartons 40HQ: 920 Cartons			
Warranty		3 years standard wa	3 years standard warranty			
Region applied		USA, Canada, Austra	USA, Canada, Australia, EU, Russia, etc.			
Industry application		Greenhouse, indoor	Greenhouse, indoor grow room, tent			
Nominal Electrica	l Ac Input*					
AC VOLTAGE	120V	208V	220V	240V	277V	
AC Current	6.07A	3.49A	3.29A	3.01A	2.59A	
AC Power	728W	726W	724W	722W	720W	
Power Factor	0.99	0.99	0.99	0.98	0.98	

^{*} At 25°C (77°F) Ambient Temperature