

PRODUCT SPECIFICATION

Orion Pro 860W



FEATURES

- 3-Channel Spectrum Control.
- Foldable Structure for Efficiency, 40% smaller package, cuts shipping costs.
- All-in-One Integrated Power Design, Hidden cables for sleek look & professional install.
- Full Spectrum + Extended UV/FR Coverage.
- Efficiency is up to 3.0 $\mu\text{mol}/\text{J}$, energy saving.

BENEFITS


1. 3-Channel Spectrum Control

- Adjust red/blue/white channels separately.
- Supports both DIY enthusiasts and commercial growers in tailoring light recipes for germination/vegetative/flowering phases.

2. Full Spectrum + Extended UV/FR

- 400-700nm PAR with 280-400nm UV & 730nm FR.
- Boosts advanced cultivation techniques.


FULL SPECTRUM & UV & FR



SPECIFICATIONS

CERTIFIED MODEL	LED AS860
PRODUCT CODE	80.01.0433
INPUT POWER	CH1:Full Spectrum 795W max;CH2:UV 25W max;CH3:Far Red 40W max
PPE(400-700nm)	3.0 μmol/J (@ 240VAC&CH1)
PP F(400-700nm)	2390 μmol/s (@ 240VAC&CH1)
DIMMING	Manual Knob & 0-10V
DAISY CHAIN	YES
INPUT VOLTAGE	AC 120V-277V
LIGHT BEAM ANGLE	120°
OPERATING TEMPERATURE	-20°C~35°C
OPERATING HUMIDITY	0~95%
HEAT DISSIPATION METHOD	passive cooling
POWER FACTOR	≥0.97
TOTAL HARMONIC DISTORTION	≤15%
CERTIFICATES	ETL / CE / EAC / FCC / DLC / ROHS / EAC
LIFETIME L90	≥ 50,000hrs
IP RATING	IP65
PRODUCT DIMENSIONS	1120x1160x56mm / 44.1x45.7x2.2 in
PRODUCT WEIGHT	8.7 KG
PACKAGING DIMENSIONS	1170x140x635mm / 46.1x5.5x25 in
GROSS WEIGHT	11 KG
LOADING QUANTITY	20GP:237 CTNS / 40HQ:624 CTNS
STANDARD WARRANTY	5 years
APPLICABLE REGIONS	Indoor or greenhouse

PRODUCT DIMENSIONS



**PROFESSIONAL
GROW LIGHTS**

nanoluxtech.com info@nanoluxtech.com



FB:@Nanolux Grow light



IG:@nanolux_official



Nanolux Catalog